

SPECIFICATIONS

Model	Transfer Medium	Max.Temp	Pump(KW)	Pump Flow(L/min)	Pump Flow(L/min)	Heating Power(KW)	Inlet/Outlet Diameter	Dimension(mm)	Approx.Net Weight(KG)
XC-TM6KW-W	Water	100°C	0.37	42	28	6	12mmx2	720*400*634	45
XC-TM9KW-W			0.37	42	28	9	12mmx4	720*400*634	46
XC-TM12KW-W			0.75	56	38	12	12mmx4	720*400*634	50
XC-TM18KW-W			1.5	160	27	9x2	1.5"x1	830*370*694	65
XC-TM24KW-W			2.2	315	26	12"x2	1.5"x1	990*450*1000	110
XC-TM36KW-W			3.75	385	28	12"x3	2"x1	990*450*1000	120
XC-TM60KW-W			3.75	385	28	12"x5	2"x1	990*450*1000	135
XC-TM6KW-O			Heat-Transfer Oil	200°C	0.37	33	22	6	3/8"x2
XC-TM9KW-O	0.37	33			22	9	3/8"x4	720*400*634	55
XC-TM12KW-O	0.75	45			30	12	3/8"x4	720*400*634	55
XC-TM18KW-O	1.5	128			21	9"x2	1.5"x1	830*370*694	68
XC-TM24KW-O	2.2	252			21	12"x2	1.5"x1	990*450*1000	110
XC-TM36KW-O	3.75	308			22	12"x3	2"x1	990*450*1000	112
XC-TM60KW-O	3.75	308			22	12"x5	2"x1	990*450*1000	135