

Scope of Application:

- To dry plastic raw materials, especially in dealing with small amount of various materials or plastics for testing.
- Saving time by avoiding waived refueling, clearing material.
- Can be used in plastic molding after tempering, which can enhance toughness, eliminate tension and improve quality of the plastic products.
- Can also be used in agricultural products (pollen, garlic, tea) or preheat or dried for electronic, electrical, electroplating, pharmaceutical, paint, printing and other products.

Structural characteristics

- With unique design of powerful air temperature and air duct system, making sure the internal temperature distribution even, baking quality is worthy of trust.
- With stainless steel shelves and circulating hot air recycling design--energy saving, durable, suitable to dry several of plastics.
- Equipped with automatic timing device for 24 hours, any time can be set in advance, to be dry.

SPECIFICATIONS

型号 Model	XC-GXD5	XC-GXD9	XC-GXD20
外部尺寸 (mm) External Dimensions	820*680*1280	820*680*1580	820*1500*1750
内部尺寸 (mm) Inner Dimensions	500*600*660	500*600*900	500*1150*1200
马达 Motor (kw)	0.375	0.375	0.75
电热 Power (kw)	4.5	6	12
盘架数 Tray Quantity	5	9	20
盘架尺寸 Tray size (mm)	585*490*50	585*490*50	585*490*50
机台重量 Weight (kg)	148	178	415
装料量 Capacity (kg)	50	90	200
材质 Tray Material	SUS430#stainless steel		
温度范围 Temperature Range	40°C ~ 200°C		
温度分布 Temperature Distribution	± 5%		

Notice:

1. When selecting the box type dryer, please according to 90% charge capacity of each model is the best choice, can up to the high economic efficiency.
2. Do not place anything on the top of the machine, in order to ensure motor and control components have enough area for radiating.

Structure Diagram :

