

FEATURE:

- ◎With small footprint and low weight, available of being placed directly onto other machines or containers for auto loading.
- ◎Microcomputer controller.
- ◎Alarm for overload and lack of material.
- ◎300G equipped with high-speed rectifier motor with delicate size and strong suction force--suitable for new materials.
- ◎400G with Induction high pressure pump--with low noise and long service time.
- ◎Cable control board design--easy to set and control with distance.
- ◎Filter for air and dust(Optional part).

SPECIFICATIONS

型号 Model		XC-X300G	XC-X400G
马达 Motor	型式 Type	碳刷式 Carbon Brush	感应式 Induction
	规格 Specification	1.1KW/1.3HP 1Φ	0.75KW/1HP 3Φ
输送能力 Conveying Capacity (Kg/h)		300	330
吸料扬程 Loading Distance(m)		3.5	4
静风压 Static Wind Pressure(mm/H ₂ O)		1300	1400
储料桶容量 Reservoir Volume(L)		7.5	7.5
送料管内径 Conveying Tube Inner Diameter(mm)		Φ38	Φ38
配料送管 Specification Of The Attached Hoses(mm)		Φ38mmx3.5m 1Pcs	Φ38mmx4m 1Pcs
外形尺寸 Dimension, L*W*H(cm)		34x34x59	45x37x66
净重约 Approx.Net Weight(kg)		12	27

Conveying capacity and loading distance are tested by ABS material; actual data may differ by plastic proportions, shapes, loading lengths and heights, pipe conditions and parameter settings.

For processing hot materials, Heat-Resistant(160°C) pipes are necessary.