

FEATURE

- Main machine separated from the hopper, easy and safe to operate.
- Independent filter for easy cleaning.
- Stainless steel hopper.
- Microcomputer control.
- Alarm for overload and short of material.
- 700G equipped with high-speed rectifier motor with delicate size and strong suction force--suitable for new materials.
- 800G/800G2 with Induction high pressure pump--with low noise and long service time.
- 800G and 800G2 are designed with auto reverse cleaning devices.

SPECIFICATIONS

型号 Model		XC-X700G	XC-X800G	XC-X800G2
马达 Motor	型式 Type	碳刷式 Carbon Brush	感应式 Induction	感应式 Induction
	规格 Specification	1.1KW/1.3HP 1Φ	1.1KW/1.5HP 3Φ	1.5KW/2HP 3Φ
输送能力 Conveying Capacity (Kg/h)		310	450	500
吸料扬程 Loading Distance (m)		4	4	5
静风压 Static Wind Pressure (mm/h ₂ O)		1550	1800	2400
储料桶容量 Reservoir Volume (L)		7.5	7.5	7.5
送料管内径 Conveying Tube Inner Diameter (mm)		Φ38	Φ38	Φ38
配料送管 Specification Of The Attached Hoses (mm)		Φ38mmx4m 2Pcs	Φ38mmx4m 2Pcs	Φ38mmx5m 2Pcs
外形尺寸 Dimension (cm)	主机 Main Frame	42x38x64	42x38x64	50x40x72
	储料桶 Hopper	36x30x56	45x32x45	45x32x45
净重约 Approx. Net Weight (kg)	主机 Main Frame	14	47	50
	储料桶 Hopper	6	7	7

Conveying capacity and loading distance are tested by ABS material; actual data may differ by plastic proportions, shapes, loading lengths and heights, pipe conditions and parameter settings.
For processing hot materials, Heat-Resistant(160°C) pipes are necessary.

We reserve the right to change specifications without prior notice.

INSTALLATION DIAGRAM

